

SJE Oil Spotter™ System

The SJE Oil Spotter™ system is designed to provide pump control and alarm notification of potentially threatening water and oil levels in simplex pumping applications.

The system features an innovative, factory-installed Oil Water Switch that senses the difference between oil and water to remove water from the tank, while preventing oil from entering the environment.

The Oil Water Switch features four probes (start level, stop level, high water level, reference for ground) and a mechanical high oil alarm float.

Common applications include elevator sump basins, transformer vaults, leachate well applications, garages or any application requiring ASME A17.1 compliance.

In normal operation, as water and oil enter the tank, the oil rises to create a floating layer on top of the water. The water level rises to reach the Start Probe, activating the pump to remove water from the tank. It continues pumping water out of the tank until the water level falls below the Stop Probe (5" pumping range).

If the water level continues to rise and reaches the High Water Probe, the red high water LED indicator illuminates and auxiliary contacts close (activating an optional Tank Alert® alarm or other remote device).

If the oil level rises to activate the mechanical High Oil Float, the red high oil LED indicator illuminates and auxiliary contacts close (activating an optional Tank Alert® alarm or other remote device).

FEATURES

- NEMA 1 rated for indoor use.
- Factory-installed 10ft power cord.
- SJE Oil Spotter™ Panel with LED indicators for:
 - High Water Indicator (red)
 - High Oil Indicator (red)
 - Pump Run Indicator (green)
 - Power Indicator (green)
- Oil Water Switch includes:
 - High Oil Float
 - High Water Probe
 - Start Probe
 - Stop Probe
 - Reference Probe
- Entire system is UL and cUL Listed to meet and/or exceed industry safety standards.
- Five-year limited warranty.



SPECIFICATIONS

VOLTAGE:

120 VAC;
230 VAC

ENCLOSURE: 8 x 8 x 4 inch (20.32 x 20.32 x 10.16 cm), NEMA 1 indoor

RECEPTACLE:

120 VAC NEMA type 5-15;
230 VAC NEMA type 6-15

MAXIMUM CURRENT: 15 amps



SJE RHOMBUS

PO Box 1708, Detroit Lakes, MN 56502
1-888-DIAL-SJE • 1-218-847-1317
1-218-847-4617 Fax

email: customer.service@sjerhombus.com
www.sjerhombus.com **B.73**

**SEE BACK FOR ORDERING INFORMATION.
SEE PRICE BOOK FOR LIST PRICE.**

SJE Oil Spotter™ System

Designed to control one 120V or one 230V single phase pump using a receptacle for easy pump connections in indoor simplex pump applications. No wiring needed.

120 VAC		Shipping Weight
Part#	Description	
1033606	SJE Oil Spotter™ System (10ft)	13 lbs
1033578	SJE Oil Spotter™ System (10ft) w/Tank Alert® AB	15 lbs
1036286	SJE Oil Spotter™ System (50ft) w/Tank Alert® AB	18 lbs

230 VAC		Shipping Weight
Part#	Description	
1037562	SJE Oil Spotter™ 230V System (10ft)	13 lbs
1037723	SJE Oil Spotter™ 230V System (10ft) w/Tank Alert® AB	15 lbs

SEE PRICE BOOK FOR LIST PRICE.

SPECIFICATIONS

VOLTAGE: 120 VAC; 230VAC

ENCLOSURE: 8 x 8 x 4 inch (15.24 x 15.24 x 10.16 cm), NEMA 1 indoor

RECEPTACLE: 120 VAC NEMA type 5-15; 230 VAC NEMA type 6-15

MAXIMUM CURRENT: 15 Amps



SJE RHOMBUS

www.sjerhombus.com
customer.service@sjerhombus.com

Call or fax your order!

1-888-DIAL-SJE (1-888-342-5753) ■ Fax 218-847-4617

*Product offering and pricing are subject to change without notice.
Please visit www.sjerhombus.com for the most current information.*